

BALL VALVES AND COCKS

- ball valves
- ball cocks
- drain cocks
- taps for tanks

Complete range of ball valves to flush the boiler, for cylinders, for a direct pump connection, compact dimension ball valves.



Drain taps are useful to drain the complete system or part of it during maintenance operations. They are normally used in the heating systems, in the powerplants (wall-hung boilers, wood-boilers, heating pumps), assembled on manifolds.

215-219

Boiler drain ball valve, nickel plated - male connection



Max working temperature	95°C
-------------------------	------

cod.	size	P [bar]	NPS	NPC	€
215 015 N00	G1/2"M	16	-	100	
219 020 N00	G3/4"M	16	-	100	

P90

Ball valve with running nut and flat gasket - female connection



Max working temperature	95°C
-------------------------	------

cod.	size	P [bar]	NPS	NPC	€
P90 025 N00	G1"F - G1"F	10	2	24	

217-221

Boiler drain ball valve, nickel plated - female connection



Max working temperature	95°C
-------------------------	------

cod.	size	P [bar]	NPS	NPC	€
217 015 N00	G1/2"F	16	-	96	
221 020 N00	G3/4"F	16	-	96	

39D

Ball valve with pump connection and male connection



Max working temperature	95°C
-------------------------	------

cod.	size	P [bar]	NPS	NPC	€
39D 020 000 R	G1"1/2F - G 1"1/2M	10	-	25	

50D.M50

Ball valve with pump connection with possibility of thermometer integration



Max working temperature 95°C

cod.	size	P [bar]	NPS	NPC	€
50 DM5 000 0R	G2"M - G2"F	10	-	-	

P40

Ball valve with pump connection and compression end



Max working temperature 95°C

cod.	size	P [bar]	NPS	NPC	€
P40 022 000	G1"1/2F - mm22	6	6	48	
P40 028 000	G1"1/2F - mm28	6	6	48	

300

Nickel plated ball valve with integrated T-joint



Max working temperature 95°C

cod.	size	P [bar]	NPS	NPC	€
300 015 N00 ●	mm15 - G1/2"	10	12	96	

301.1

Nickel plated ball valve with handle - compression end



Max working temperature 95°C

cod.	size	P [bar]	NPS	NPC	€
301 015 N00 1 ●	mm15 - G1/2"	10	35	280	

38D.1T

new

Ball valve with pump connection with possibility of thermometer integration - DN25



Max working temperature 95°C

cod.	size	handle colour	P [bar]	NPS	NPC	€
38D 025 000 1T	G1"1/2 F - G 1"F	red	10	-	16	
38D 025 000 1BT ●	G1"1/2 F - G 1"F	blue	10	-	16	

P41

Ball valve with pump connection and female connection



Max working temperature 95°C

cod.	size	P [bar]	NPS	NPC	€
P41 025 000	G1"1/2F - G1"F	6	6	48	

301

Nickel plated ball valve with handle - compression end



Max working temperature 95°C

cod.	size	P [bar]	NPS	NPC	€
301 015 N00 ●	mm15 - G1/2"	10	35	280	

303

Nickel plated ball valve - compression end



Max working temperature 95°C

cod.	size	P [bar]	NPS	NPC	€
303 015 N00 ●	mm15 - G1/2"	10	50	400	

P	Max working pressure
N°P/S	Pieces per box
N°P/C	Pieces per carton



●	Article on request
---	--------------------

P	Max working pressure
N°P/S	Pieces per box
N°P/C	Pieces per carton



●	Article on request
---	--------------------

303.1

Nickel plated ball valve - compression end



Max working temperature 95°C

cod.	size	P [bar]	NPS	NPC	€
303 015 N00 1 ●	mm15 - G1/2"	10	50	400	

W09

Drain cock with adjustable plastic hose connection (Hose diameter less than 11mm)



Max working temperature 95°C

cod.	size	P [bar]	NPS	NPC	€
W09 010 N00	G3/8"	16	30	600	

P59

Drain cock with adjustable plastic hose connection - with handle (Hose diameter less than 9mm)



Max working temperature 95°C

cod.	size	P [bar]	NPS	NPC	€
P59 008 N00	G1/4"	10	30	600	
P59 010 N00	G3/8"	10	30	600	

P82

Drain cock - with hose connection and plug



Max working temperature 95°C

cod.	size	P [bar]	NPS	NPC	€
P82 015 N00	G1/2" - G3/4"	16	10	40	

500

Cut taps for thick liquids (Eg. honey), chrome plated



Max working temperature 60°C

cod.	size	P [bar]	NPS	NPC	€
500 040 C00	G1"1/2	6	-	50	
500 050 C00	G2"	6	-	30	

W33

Drain cock with adjustable brass hose connection



Max working temperature 95°C

cod.	size	P [bar]	NPS	NPC	€
W33 008 000 T ●	G1/4" - G3/4"	16	30	240	

P32

Drain cock for solar system - with hose connection and plug



Max working temperature 150°C

cod.	size	P [bar]	NPS	NPC	€
P32 015 000	G1/2"M	16	10	40	