

# FITTINGS

- running nut
- elbows
- T joint



V38.09



P93



P93.N



23B.C



23B



P94.L1



V20.0



45D.DN32

**P93.N**

Fitting with running nut and flat washer - nickel plated



Max working temperature 100 °C

cod.	size	P [bar]	NPS	NPC	€
P93 015 N00	G3/4" F - G1/2" M	25	20	80	
P93 020 N00	G1" - G3/4" M	25	16	64	
P93 025 N00	G1"1/4 - G1" M	25	8	64	
P93 032 N00	G1"1/2 - G1"1/4 M	25	4	32	

**P93**

Fitting with running nut and flat washer



Max working temperature 100 °C

cod.	size	P [bar]	NPS	NPC	€
P93 015 000	G3/4" F - G1/2" M	25	20	80	
P93 020 000	G1" - G3/4" M	25	16	64	
P93 025 000	G1"1/4 - G1" M	25	8	64	
P93 032 000	G1"1/2 - G1"1/4 M	25	4	32	

**Y77.2**

Fitting with running nut and flat washer



Max working temperature 110 °C

cod.	size	P [bar]	NPS	NPC	€
Y77 A20 000 2	G3/4" - G3/4" M	16	20	80	
Y77 A25 000 2	G1" - G1" M	16	20	80	

**Y77.N2**

Fitting with running nut and flat washer - nickel plated



Max working temperature 110 °C

cod.	size	P [bar]	NPS	NPC	€
Y77 A20 N00 2	G3/4" - G3/4" M	16	20	80	
Y77 A25 N00 2	G1" - G1" M	16	20	80	

**541**

Fitting with running nut and flat washer - side holes for flowmeter plumbing



Max working temperature 90 °C

cod.	size	P [bar]	NPS	NPC	€
541 010 000	3/8" M - 3/4" F	16	20	80	
541 015 000	1/2" M - 3/4" F	16	14	56	
541 020 000	3/4" M - 1" F	16	14	56	
541 025 000	1" M - 1"1/4 F	10	8	64	
541 032 000	1"1/4" M - 1"1/2 F	10	6	24	
541 040 000	1"1/2" M - 2" F	8	4	16	
541 050 000	2" M - 2"1/2 F	8	2	16	

**44D.DN25**

2 fittings with flat gasket - DN25



Max working temperature 90 °C

cod.	size	P [bar]	NPS	NPC	€
44D 025 000	G1" F - G1"1/2 F	10	-	-	

**44D.DN32**

2 fittings with flat gasket - DN32



Max working temperature 90 °C

cod.	size	P [bar]	NPS	NPC	€
44D 032 000	G 1"1/4 F - G 2" F	10	-	-	

**V38.09** new

Fitting F. with running nut and flat gaskets




Max working temperature 100 °C

cod.	size	P [bar]	NPS	NPC	€
V38 025 000 09	G1" F - G1"1/2 F	10	-	-	

**036.7**

Hexagonal and removable running nut



Max working temperature 140 °C

cod.	size	NPS	NPC	€
036 020 007	G3/4"	-	-	
036 025 007	G1"	-	-	
036 032 007	G1"1/4	-	-	
036 040 007	G1"1/2	-	-	
036 050 007	G2"	-	-	

**036.7N**

Hexagonal and removable running nut - nickel plated



Max working temperature 140 °C

cod.	size	NPS	NPC	€
036 020 N07	G3/4"	-	-	
036 025 N07	G1"	-	-	
036 032 N07	G1"1/4	-	-	
036 040 N07	G1"1/2	-	-	
036 050 N07	G2"	-	-	

**188.3**

Hexagonal running nut



Max working temperature 140 °C

cod.	size	NPS	NPC	€
188 040 003	G1"1/2	-	-	

**188.3N**

Hexagonal running nut - nickel plated



Max working temperature 140 °C

cod.	size	NPS	NPC	€
188 040 N03	G1"1/2	-	-	

P	Max working pressure
N°P/S	Pieces per box
N°P/C	Pieces per carton



●	Article on request
---	--------------------


P	Max working pressure
N°P/S	Pieces per box
N°P/C	Pieces per carton



●	Article on request
---	--------------------

### 032.7

Hexagonal nut for copper pipe English type




Max working temperature 140 °C

cod.	size	NPS	NPC	€
032 015 007	mm15	-	-	
032 022 007	mm22	-	-	
032 028 007	mm28	-	-	

### 032.7.N

Hexagonal nut for copper pipe English type - nickel plated




Max working temperature 140 °C

cod.	size	NPS	NPC	€
032 015 N07 ●	mm15	-	-	
032 022 N07 ●	mm22	-	-	
032 028 N07 ●	mm28	-	-	

### 032.7.C

Hexagonal nut for copper pipe English type - chrome plated




Max working temperature 140 °C

cod.	size	NPS	NPC	€
032 015 C07 ●	mm15	-	-	
032 022 C07 ●	mm22	-	-	
032 028 C07 ●	mm28	-	-	

### 032.8

Brass olive for copper pipe




Max working temperature 95°C

cod.	size	type	NPS	NPC	€
032 015 008	15mm	English	-	-	
032 015 008 I	15mm	Irish	-	-	
032 022 008	22mm	English	-	-	
032 022 008 I	22mm	Irish	-	-	
032 028 008	28mm	English	-	-	
032 028 008 I	28mm	Irish	-	-	

### 038.12

Copper olive for copper pipe



Max working temperature 95°C

cod.	size	type	NPS	NPC	€
038 015 012	15mm	English	-	-	
038 022 012	22mm	English	-	-	
038 028 012	28mm	English	-	-	

### 16B

Running nut M-M with integrated O-ring (code xxx xxx Nxx x nickel plated)



Max working temperature 95°C

cod.	size	P [bar]	NPS	NPC	€
16B 025 000 1	G3/4" - G1" racc.	10	25	100	
16B 025 N00 1 ●	G3/4" - G1" racc.	10	25	100	

### 12D-47D.A

Connection 3/4" coupling and compression end with assembled olive and O-ring



Max working temperature 140 °C

cod.	size	P [bar]	NPS	NPC	€
12D 015 000	mm15 - G3/4" M	16	-	-	
12D 015 000 M	G1/2" M - G3/4" M	16	-	-	
12D 018 000	mm18 - G3/4" M	16	-	-	
12D 020 000 M	G3/4" M - G3/4" M	16	-	-	
12D 022 000	mm22 - G3/4" M	16	-	-	
12D 025 000 M	G1" M - G3/4" M	16	-	-	
47D 020 004 A	mm22 - G3/4" F	16	-	-	

### V36.I2

**new**

2 Adapter fittings between DN25 groups and DN32 manifolds - flat gasket



Max working temperature 110 °C

cod.	size	P [bar]	NPS	NPC	€
V36 050 000 I2	G2" M - G1" 1/2 F	10	2	-	

### V38.07

**new**

Fitting F.M. with flat gaskets



Max working temperature 100 °C

cod.	size	P [bar]	NPS	NPC	€
V38 025 000 07	G1" F - G1" 1/2 M	16	-	-	

### 23B

Pump connection elbow with removable running nut - length 60mm



Max working temperature 95°C  
Length 41 mm

cod.	size	P [bar]	NPS	NPC	€
23B 040 000	G1" 1/2 - Rp 3/4"	10	5	10	

### 23B.C

Pump connection elbow with removable running nut - length 41mm



Max working temperature 95°C  
Length 60 mm

cod.	size	P [bar]	NPS	NPC	€
23B 040 000 C	G1" 1/2 - Rp 3/4"	10	5	10	

### 02B

Elbow F.M. with lock nut and integrated O-ring (cod. xxx xxx Nxx nickel plated)



Max working temperature 95°C

cod.	size	P [bar]	NPS	NPC	€
02B 020 000	RP3/4" - G3/4"	10	-	-	
02B 020 N00 ●	RP3/4" - G3/4"	10	-	-	

P	Max working pressure
N°P/S	Pieces per box
N°P/C	Pieces per carton



●	Article on request
---	--------------------

P	Max working pressure
N°P/S	Pieces per box
N°P/C	Pieces per carton



●	Article on request
---	--------------------



**V20.0**

T fitting with two running nut. Connections distance 62mm. Flat washer included



Max working temperature 100 °C

cod.	size	P [bar]	NPS	NPC	€
V20 025 000	G1" - G1"	10	-	-	

**055.P**

Nylon plug with O-ring



Max working temperature 95 °C

cod.	size	NPS	NPC	€
055 008 002 P01	G1/4"	-	-	

**P23**

Fitting - M.M. - with 1/2" plug suitable for probe holder



Max working temperature 95 °C

cod.	size	P [bar]	NPS	NPC	€
P23 015 000	G1/2"	16	20	160	
P23 020 000	G3/4"	16	14	84	
P23 025 000	G1"	16	10	60	

**40D**

Extensions with flat sealing, dimension 272 mm



Max working temperature 140 °C

cod.	size	P [bar]	NPS	NPC	€
40D 040 000	G1"1/2 - 272mm	10	-	16	

**45D.DN25**

T-joint - DN25




Max working temperature 140 °C

cod.	size	P [bar]	NPS	NPC	€
45D 040 00	G1"1/2F - G1"1/2M - G1"F	10	-	-	

**650**

Plug with collar (code xxx xxx Nxx nickel-plated)



Max working temperature 95 °C

cod.	size	NPS	NPC	€
650 015 000	G1/2"	-	-	
650 020 000	G3/4"	-	-	
650 015 N00	G1/2"	-	-	
650 020 N00	G3/4"	-	-	

**P28.I4**

Probe holder fitting - seal on fitting



Max working temperature 95 °C  
Probe diameter 6 mm

cod.	size	P [bar]	NPS	NPC	€
P28 015 000 I4 ●	G1/2"	16	10	50	

**40D.DN32**

Extensions with flat sealing, dimension 280 mm



Max working temperature 140 °C

cod.	size	P [bar]	NPS	NPC	€
40D 050 000	G2"M - 280mm	10	-	16	

**45D.DN32**

T-joint - DN32




Max working temperature 140 °C

cod.	size	P [bar]	NPS	NPC	€
45D 050 000 ●	G 2"F - G 2"M - G 1"1/4F	10	-	-	

**175.17**

Hose connector



Max working temperature 95 °C

cod.	size	NPS	NPC	€
175 015 017 I	G3/4"	-	-	

**P28.I1**

Probe holder fitting - seal on probe



Max working temperature 95 °C  
Probe diameter 6 mm

cod.	size	P [bar]	NPS	NPC	€
P28 015 000 I1 ●	G1/2"	16	20	100	

**40D.2**

Extensions with flat sealing, dimension 180 mm



Max working temperature 140 °C

cod.	size	P [bar]	NPS	NPC	€
40D 040 002	G1"1/2 M - 180mm	10	-	16	

P	Max working pressure
N°P/S	Pieces per box
N°P/C	Pieces per carton



●	Article on request
---	--------------------

P	Max working pressure
N°P/S	Pieces per box
N°P/C	Pieces per carton



●	Article on request
---	--------------------

### 40D.2.DN32

Extensions with flat sealing, dimension 180 mm



Max working temperature 140 °C

cod.	size	P [bar]	NPS	NPC	€
40D 050 002	G2" M - 180mm	10	-	16	

### 47D

Copper pipe for two solar pump installation for east/west regulation or double tank use. Pipe distance 230mm



Max working temperature 140 °C

cod.	size	P [bar]	NPS	NPC	€
47D 020 000 M ●	G3/4" M - mm22 M	10	-	10	
47D 022 000 K ●	mm22 M - mm22 M	10	-	10	
47D 020 000 K ●	G3/4" M - G3/4" M	10	-	10	
47D 020 000 MK ●	G3/4" M - G3/4" F	10	-	10	

### 560

Rubber gasket for suitable for food industry



Max working temperature 60 °C

cod.	size	NPS	NPC	€
560 010 000	22,5 - 17 - 2	-	-	
560 015 000	30 - 21 - 3	-	-	
560 020 000	36 - 23 - 3	-	-	
560 025 000	45 - 33 - 3	-	-	
560 032 000	55 - 42 - 3	-	-	
560 040 000	55 - 48 - 3	-	-	
560 050 000	68 - 58,6 - 2	-	-	

### 40D.L

L-extensions with flat sealing, dimension 272 mm



Max working temperature 140 °C

cod.	size	P [bar]	NPS	NPC	€
40D 040 000 L	G1" 1/2 M - G3/4" - 272mm	10	-	16	

### 570

O-ring for cod. 500



Max working temperature 95 °C

cod.	size	NPS	NPC	€
570 040 000	46,04 - 3,53	-	-	
570 050 000	60 - 2,62	-	-	

### 575

Fiber washer



Max working temperature 60 °C

cod.	size	NPS	NPC	€
575 020 000	24,2 - 18 - 2	-	-	
575 025 000	30 - 21 - 3	-	-	
575 032 000	39 - 25 - 2	-	-	
575 040 000	45 - 33,3 - 2	-	-	
575 050 000	56,5 - 41 - 2	-	-	

P	Max working pressure
N°P/S	Pieces per box
N°P/C	Pieces per carton



●	Article on request
---	--------------------

P	Max working pressure
N°P/S	Pieces per box
N°P/C	Pieces per carton



●	Article on request
---	--------------------